

# PCI-P16X16

---

## User Manual

### **Warranty**

All products manufactured by ICP DAS are warranted against defective materials for a period of one year from the date of delivery to the original purchaser.

### **Warning**

ICP DAS assume no liability for damages consequent to the use of this product. ICP DAS reserves the right to change this manual at any time without notice. The information furnished by ICP DAS is believed to be accurate and reliable. However, no responsibility is assumed by ICP DAS for its use, nor for any infringements of patents or other rights of third parties resulting from its use.

### **Copyright**

Copyright 2017 by ICP DAS. All rights are reserved.

### **Trademark**

The names used for identification only may be registered trademarks of their respective companies.

# Tables of Contents

<b>1.</b>	<b>Linux Software Installation .....</b>	<b>3</b>
1.1	LINUX DRIVER INSTALLING PROCEDURE.....	3
1.2	LINUX DRIVER UNINSTALLING PROCEDURE.....	3
<b>2.</b>	<b>PCI-P16X16 Demo Programs For Linux.....</b>	<b>4</b>
2.1	DEMO CODE "DIO.C" .....	4

---

## 1. Linux Software Installation

The PCI-P16R16/P16C16/P16POR16 can be used in linux kernel 2.4.X and 4.X.X. For Linux O.S, the recommended installation and uninstall steps are given in Sec 1.1 ~ 1.2

---

### 1.1 Linux Driver Installing Procedure

Step 1: Copy the linux driver "ixpci.tar.gz"(version 0.7.4 or later version) in directory "NAPDOS\Linux" of the CD or from our company website <http://ftp.icpdas.com/pub/cd/iocard/pci/napdos/linux/ixpci.tar.gz> to the linux host that you want to install driver.

Step 2: Decompress the tarball "ixpci.tar.gz".

Step 3: Type `cd' to the directory containing the package's source code and type `./configure` to configure the package for your system.

Step 4: Type `make` to compile the package.

Step 5: Type `./ixpci.inst` to install the PCI driver module and build the device file "ixpciX" in the device directory "/dev" automatically.

---

### 1.2 Linux Driver Uninstalling Procedure

Step 1: Type `cd` to the directory containing the package's source code.

Step 2: Type `./ixpci.remove` to remove the PCI driver module.

---

## 2. PCI-P16X16 Demo Programs For Linux

All of demo programs will not work normally if PCI linux driver would not be installed correctly. During the installation process of PCI linux driver, the install-scripts “ixpci.inst” will setup the correct kernel driver. After driver(version 0.7.4 or the later driver version) compiled and installation, the related demo programs, declaration header files for different development environments are presented as follows.

Table 3.1

Driver Name	Directory Path	File Name	Description
lxpci-0.7.4 (or later version)	examples/ pcip16x16	dio.c	DO/DI Demo

---

### 2.1 Demo code “dio.c”

This demo program is used to show the DI/DO.