

WP-9x21-CE7 OS Update History

Last update 2016/07/14

Features	Supported	Description
Windows CE 7.0 Core OS	Yes	
OS Language	Yes	WP-9x2x-ML: Multi-language <ul style="list-style-type: none"> - English - German - Russian - French - Spanish - Italian - Korean - Simplified Chinese - Traditional Chinese
.NET Compact Framework 3.5	Yes	V3.5.7283.0 for Visual Studio .Net 2008
SQL CE 3.5	Yes	SQL CE 3.5 (3.5.5386.0)
FTP Server	Yes	
HTTP Server	Yes	
Telnet	Yes	
Printer	No	
Display Resolution	Yes	800 x 600, 1024 x 768
Touch Panel	Yes	Support for touch panels using the RS-232 and USB interfaces
Multiport Serial Communication Module The maximum number of ports that can be used is 16. (i.e., 4 slots * 4 ports per module = max. of 16 ports)	Yes	Supported modules: I-9114 (RS232 * 4) I-9144 (RS485 * 4)
Real Time Interrupt	Yes	Interrupt error offset $\pm 230\mu\text{s}$
3G dial function	Yes	

Software and Hardware Compatibility

Software		Hardware
OS	Eboot	V1.51
V1.0.3.1 [2017/05/02]	V1.3.3.0	Yes

Table of Contents

WP-9x21-CE7 OS Version 1.0.3.1 - Release Notes [2017/05/02]4

WP-9x21-CE7 OS Version 1.0.3.1 - Release Notes [2017/05/02]

Abstract

This OS release adjust interrupt function and add 3G dialing function. The Eboot now will not format full flash when reinstall OS but only OS block.

Bugs Fixed and Improvements

- Adjust interrupt accuracy to $\pm 230\mu\text{s}$.
- Add 3G dialing function.

Eboot

V1.3.3.0 only format OS block in Flash when reinstall OS (V1.3.3.0, 2017/04/05)

Software and Hardware Compatibility

Software		Hardware
OS	Eboot	V1.51
V1.0.3.1 [2017/05/02]	V1.3.3.0	Yes

WinPAC Utility and WinPAC SDK

- PACSDK DLL Version 4.4.0.4 (Released on 2017/01/25)
- PAC Utility Version 1.2.1.8 (Released on 2016/06/15)