

---

## The Wincon-8x47 Supports Max. 32 Modbus TCP/IP Connections Since Its Driver Version 4.03

---

**If the controller is Wincon-8347 / 8747 (Wincon with 2 ethernet ports), the OS image of the W-8x47 must use the version released at Jul.01,2008, or its Ethernet communication will not work correctly.**

**(Please refer to [www.icpdas.com](http://www.icpdas.com) > FAQ > Software > ISaGRAF > 094 )**

The W-8347 / 8747 / 8346 / 8747 supports Max. 32 Modbus TCP/IP connections since its driver version 4.03 . For example, if each PC / HMI / SCADA is using two Modbus TCP/IP connections to connect the W-8x47, then max. 16 PC / HMI / SCADA can connect to this W-8x47 at the same time. If each PC / HMI / SCADA is using four Modbus TCP/IP connections to connect the W-8x47, then max. 8 PC / HMI / SCADA can connect to this W-8xx7 at the same time. If each PC / HMI / SCADA is using only one Modbus TCP/IP connections to connect the W-8x47, then max. 32 PC / HMI / SCADA can connect to this W-8x47 at the same time.

Please obtain the new released ISaGRAF Driver, Manual , FAQ and Data Sheet at the following web.

Driver: [www.icpdas.com](http://www.icpdas.com) > ISaGRAF SoftLogic PAC > Driver

Manual: [www.icpdas.com](http://www.icpdas.com) > ISaGRAF SoftLogic PAC > Manual

FAQ: [www.icpdas.com](http://www.icpdas.com) > ISaGRAF SoftLogic PAC > FAQ

Data Sheet: [www.icpdas.com](http://www.icpdas.com) > ISaGRAF SoftLogic PAC > Data Sheet